

	 <p data-bbox="703 757 1426 846">           b = width of the housing with the O-Ring            b1 = width of the housing with one anti-extrusion ring and the O-Ring            b2 = width of the housing with two anti-extrusion rings and the O-Ring         </p>				
O - Ring Section ds (mm)	1,80 ± 0,08	2,65 ± 0,09	3,55 ± 0,10	5,30 ± 0,13	7,00 ± 0,15
Housing depth t (mm)	1,40	2,20	2,90	4,5	5,9
Deformation of the O - Rings (mm)	0,26 to 0,58	0,26 to 0,64	0,4 to 0,85	0,57 to 1,08	0,80 to 1,35
Deformation of the O - Rings (%)	15 to 31	10 to 23	11 to 23	11 to 20	11 to 19
Housing depth b (mm)	2,4 to 2,6	3,6 to 3,8	4,8 to 5,0	7,2 to 7,4	9,6 to 9,8
b1 with one anti-extrusion ring (mm)	3,5 to 3,7	4,7 to 4,9	5,8 to 6,0	8,7 to 8,9	12,0 to 12,2
b2 with two anti-extrusion rings (mm)	4,6 to 4,8	5,8 to 6,0	6,8 to 7,0	10,2 to 10,4	14,4 to 14,6
Radius ri (mm)	0,2 to 0,4	0,2 to 0,4	0,4 to 0,8	0,4 to 0,8	0,4 to 0,8